



Starpatch Concrete Products

#5-6420 Beresford Street,
Burnaby, B.C. V5E 1B6
Phone: (604) 433-7355 Fax: (604) 433-7358

Sacking Mortar

Description: Made especially for use on walls to fill and finish minor imperfections to create a smooth and professional looking job to leave as is or to paint. **Sacking Mortar** is very easy to apply using either a rubber float burlap sack or Styrofoam block. **Sacking Mortar** is available in three different shades Reg., #2, and #3). Imperfections should not exceed 1/8".

Recommended: Use for sacking and repairing of vertical surfaces either inside or outside. Where ever an architectural finish is required. Great for sacking walls with slight imperfections such as air holes or honey combs left from inadequate vibration. Ideal for sacking walls of entranceways and stairwells.

Advantages:

- Easy to apply using a rubber float or sack.
- Easy to mix, using only water.
- Consistent quality making it cost-effective.
- Non-shrink tendencies under normal conditions when instructions are followed.
- Approved for architectural finishes.
- Colour match your ready mix.

Surface Preparation: Concrete or masonry surface (interior or exterior) must be clean and free of all dust, grease and other foreign material. Saturate the area with water thoroughly; remove any standing water prior to the application of sacking mix.

Mixing: Please use the chart below to mix to your desired consistency. Do not exceed 5.4 liters per bag. When using as a skim coat use **900X** with water at a 3:1 ratio (3 parts water 1 part **900X**).

Consistency	% of Water	Water/22.7kg
Dry Pack	15% - 18%	3.4 - 4.1 liters
Plastic	19% - 20%	4.3 - 4.5 liters
Slurry	23%	5.2 liters

Application: Fill air holes and imperfections having maximum depth of approximately 1/8" using a rubber float, burlap sack or blue Styrofoam block. Use wrist motion to pack mortar into the small holes leaving the treated surface smooth and flush with the adjacent

surface. To smooth out walls for painting, apply dry **Sacking Mortar** to a burlap sack and use wrist action to completely finish surface. Ensure surface remains damp during application for best results. All excess material must be removed from the wall.

Test Results: Test reports, evaluation and Material Safety Data Sheet are available on request.

Bucket Life: Approximately 1½ to 2 hours depending on temperature and humidity.

Curing Time: Depending on humidity and temperature, usually 2 to 4 hours. **Sacking Mortar** is ready for painting after 10 days of curing.

Limitations: Temperature at time of application may not be lower than 5°C/41°F. Not to be used to repair off-set joints.

Shelf Life: One year in original unopened bag in dry storage.

Colour: Concrete grey. Available in Reg., #2(lighter) or #3(even lighter). Final colour will be effected by amount of water used during application and application method.

Packaging: 22.7kg/50lbs. bag.

Caution: Contains cement, a polymer and other additives which may cause skin irritation. In case of skin or eye contact, wash thoroughly with water. Please consult the MSDS for detailed safety and handling instructions. In case of eye contact consult with nearest physician. **KEEP OUT OF REACH OF CHILDREN.**

Warranty: Starpatch Concrete Products warrants that if its products prove to have manufacturing defects and Starpatch is notified of such within 6 months from date of Starpatch shipping, Starpatch will replace the defective products F.O.B. factory. Such product replacement shall constitute the sole and exclusive remedy for any claim under this warranty. This warranty is in lieu of all other warranties, expressed, implied or statutory and is strictly limited to its terms. Starpatch makes no warranty of merchantability or suitability of its products for any particular purpose. Starpatch sells its products upon the condition that the customers shall conduct their own tests to determine the suitability of the products for the customers intended purposes. Under no circumstances will Starpatch be liable for economic, special, incidental or consequential damages or losses of any kind whatsoever arising out of or occasioned by the selection, use, installation or replacement of this product.

Starpatch Concrete Products, Burnaby, BC.
Phone (604) 433-7355